



Transform wasted attic space into fantastic loft living



VELUX GGL Centre-Pivot roof window



Beautifully engineered for a lifetime of use, the GGL is ideal for in-reach attic situations.

- A short pull on the top control bar allows filtered background ventilation even while the window remains shut.
- A second pull on the control bar allows the window to rotate for maximum ventilation – and up to 180° for cleaning the outer pane from inside the room.
- Quality lacquered pine sash & frame.
- Complete with outer aluminium cappings and flashings for corrugated iron or tile roofs.
- Available in 4 sizes.
- High Performance double glazing as standard.
- Insect screen available as extra.

Technical Performance	
U-value†	✓
Roof window	1.40
Glass only	1.10
Solar Heat Gain Co-efficient†	✓
Roof window	0.28
Glass only	0.28
Bushfire^	✓
BAL40	✓
WERS max 5 stars (summer rating)	★★★★★
Australian Standards	✓
AS4285 AS1288	
AS3959 AS1530.1‡	

Blinds for GGL

Manual Blockout Manual Venetian

• All blinds available in white • Now even easier to fit using VELUX **Pick&Click!**™ System.

VELUX GDL CABRIO® Balcony roof window

When closed it looks just like an ordinary skylight – but within seconds it opens up to a fantastic roof top balcony. Bottom section moves forward and locks upright with integral banister railings to form a sturdy balcony surround. Contact VELUX for full details.

* For roofs below 15° pitch, skylights need to be raised to 15° and custom flashed. VELUX can assist with technical advice and drawings. (NB: build-up not permitted in Bushfire areas.) † U-value (W/m²K) and SHGC calculated according to EN 14351-1:2006 + A1:2010 (window size 1140mm x 1400mm). ^ Bushfire testing applicable to GGL in roof pitch 18°-75° and GHL in roof pitch 18°-55°. Roof window only. Custom-made flashing required. Additional mesh protection may be required for opening apertures (consult local council). ‡ Roof Window in closed position.



VELUX GHL Dual action roof window



Developed for use in attics with shallower pitched roofs to maximise roof top views. For within-reach situations only.

- Opens in two ways: the bottom handle allows for top-hung opening; while a short pull on the top control bar operates the filtered vent flap for background ventilation even while the window is shut. A longer pull allows the sash to rotate 180° for ease of cleaning the outer pane from inside the room.
- Quality lacquered pine sash & frame.
- Complete with outer aluminium cappings and flashings for corrugated iron or tile roofs.
- Available in 4 sizes.
- High Performance double glazing as standard.
- Insect screen available as extra.

Technical Performance	
U-value†	✓
Roof window	1.40
Glass only	1.10
Solar Heat Gain Co-efficient†	✓
Roof window	0.28
Glass only	0.28
Bushfire^	✓
BAL40	✓
WERS max 5 stars (summer rating)	★★★★★
Australian Standards	✓
AS4285 AS1288	
AS3959 AS1530.1‡	

Blinds for GHL

Manual Blockout Manual Venetian

